



# SERIES

## FLOORING<sup>PRO</sup>

UK FLOORING DIRECT



### Product Data Sheet

**LAM-SEHB-8-001**

Scan the QR code for fast access to this floor online

## Series Woods Professional 8mm Herringbone Laminate Flooring Roma Oak

Series Woods Professional 8mm Herringbone Laminate Flooring Roma Oak looks and feels just like a hardwood floor but thanks to a tough top layer, it's ideal for a busy household and the rigours of day-to-day life. Boasting an AC4 rating, it's suitable for most rooms in the home, and for various commercial settings, such as small offices and hotel rooms, and requires only regular vacuuming and occasional damp mopping to stay looking its best. At 8mm thick, Herringbone Laminate Roma Oak is suitable for heavy domestic use. Complete with a click system which makes installation a quick and easy process - the perfect option for keen DIYers. Looked after with care, this premium laminate floor is ready for lasting use.

Our Herringbone Roma Oak Laminate Flooring provides the soft and light textures of oak to any room with the eye-catching design of herringbone flooring. Featuring an authentic textured surface that includes realistic knots and lines which enhances the oak effect, this European-made floor combines the gorgeous look and feel of wood with the practicality of laminate. With 133mm boards, this herringbone flooring is perfect for a medium and large room to utilise the full effect of the pattern.

### Product Details

Code:	LAM-SEHB-8-001
Brand:	Series Woods Professional
Construction:	Laminate
Surface:	Authentic Textured
Profile:	Click System
Edge profile:	Bevelled on 4 sides
Thickness:	8mm
Width:	133mm
Length:	665mm
Coverage per pack:	1.238
AC rating:	AC4 - Heavy Domestic

### Warranty

Residential:	25 Years
Commercial:	N/A

### Installation

Floated on underlay:	Yes
Over underfloor heating:	Yes, Water Systems

### Technical

Water rating:	Moisture Protection
Technical Class:	32
Fire resistance:	EN 13501
Formaldehyde emission:	EN 717-1
Slip resistance:	DS
Thermal resistance/conductivity:	EN 12667
Resistance to staining:	EN 438
Wear resistance:	EN 13329
Effects of furniture leg:	EN 424
Effects of castor chair:	EN 425
Light fastness:	EN 13329
VOC emissions:	ISO 16000
Thickness swelling:	EN 13329
Tolerance:	EN 13329

### UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ  
Tel: 02476 012840 | Fax: 02476 397828  
info@ukflooringdirect.co.uk  
ukflooringdirect.co.uk

© 2020. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.