



UK **FLOORING DIRECT**



Product Data Sheet

LAM-TL-8-005

Scan the QR code for fast access to this floor online

City City 8mm Laminate Tile Deco Graphite

Fit a sense of sophistication into any room with City 8mm Laminate Tile Deco Graphite. With a gorgeous grey surface that's delightfully accented by distressed tones to evoke a sense of real stone, this quality-made floor packs all the practical benefits of laminate into a stylish and modern package.

This flooring comes with a textured surface and features four bevelled edges that create an even truer imitation of genuine stone tiling when the floor is finished. With 605mm x 282mm tiles that are compact, easy to fit and a fast and fuss free project possible for avid DIYers thanks to click system technology, there's no reason not to add this classic stone look into your home.

Thanks to its AC4 Heavy Domestic rating and a 20-year warranty, City 8mm Laminate Tile Deco Graphite is ready to withstand the busiest homes and the highest traffic areas, from your hallways to your dining rooms.

Product Details

| | |
|--------------------|----------------------|
| Code: | LAM-TL-8-005 |
| Brand: | City |
| Construction: | Laminate |
| Surface: | Authentic Textured |
| Profile: | Click System |
| Edge profile: | Bevelled on 4 sides |
| Thickness: | 8mm |
| Width: | 282mm |
| Length: | 605mm |
| Coverage per pack: | 2.047 |
| AC rating: | AC4 - Heavy Domestic |

Warranty

| | |
|--------------|----------|
| Residential: | 20 years |
| Commercial: | N/A |

Installation

| | |
|--------------------------|--------------------|
| Floated on underlay: | Yes |
| Over underfloor heating: | Yes, Water Systems |

Technical

| | |
|----------------------------------|--------------|
| Water rating: | N/A |
| Technical Class: | 32 |
| Fire resistance: | Cfl-s1 |
| Formaldehyde emission: | E1 |
| Slip resistance: | DS |
| Thermal resistance/conductivity: | EN 12667 |
| Resistance to staining: | EN 438 |
| Wear resistance: | EN 13329 |
| Effects of furniture leg: | EN 424 |
| Effects of castor chair: | EN 425 |
| Light fastness: | EN 20101-A02 |
| VOC emissions: | EN 717-1 |
| Thickness swelling: | EN 13329 |
| Tolerance: | EN 13329 |

UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ
Tel: 02476 012840 | Fax: 02476 397828
info@ukflooringdirect.co.uk
ukflooringdirect.co.uk

© 2020. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.