



Product Data Sheet

VIN-CLIC-PL-432

Scan the QR code for fast access to this floor online

ParquetVinyl Amazon Valley Plank Luxury Rigid Core Click Vinyl Flooring

With its medium grain and warm oak tone, ParquetVinyl Amazon Valley Plank Luxury Click Vinyl offers the classic good looks of a traditional-style wood-effect floor along with all the practical benefits of rigid core vinyl.

Featuring an Authentic Textured surface that follows the wood grain and surface markings of the décor layer and bevelled edges for the best in realism, this style comes in an extra-wide (223mm), long length (1513mm) plank ideally suited to larger rooms. Thanks to a stable rigid core, ParquetVinyl is less likely to indent and mark, its water-resistant construction and highly-durable, simple to maintain surface making ParquetVinyl Amazon Valley Plank Luxury Click Vinyl Flooring ready for any situation.

Coming with a 35-year residential warranty this is one tough floor, achieving an AC 6 heavy commercial wear rating for complete peace of mind. Fast-to-fit, thanks to a DIY click joint and rigid construction that just needs a flat subfloor, ParquetVinyl Amazon Valley Plank Luxury Click Vinyl Flooring is so stable it's safe to use with underfloor heating or in areas exposed to changes in humidity and temperature. UV-resistant too, it's great for use in conservatories.

Product Details

Code:	VIN-CLIC-PL-432
Brand:	ParquetVinyl
Construction:	SPC
Surface:	Authentic Textured
Profile:	Click System
Edge profile:	Bevelled on 4 sides
Wear layer:	0.70mm
Thickness:	4mm
Width:	223mm
Length:	1513mm
Coverage per pack:	2.36m ²
AC rating:	AC6 - Heavy Commercial

Warranty

Residential:	35 Year
Commercial:	20 Years

NB: Please ask for full warranty terms and conditions

Installation

Floated on underlay:	Yes
Over underfloor heating:	Electric & Water Systems up to 27 °C

Technical

Water rating:	Waterproof
Technical Class:	Class 34
Fire resistance:	Bfl-S1
Formaldehyde emission:	E1
Slip resistance:	EN 13893
Thermal resistance/conductivity:	EN 14041
Resistance to staining:	EN 14041
Wear resistance:	EN 14041

UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ
Tel: 02476 012840 | Fax: 02476 397828
info@ukflooringdirect.co.uk
ukflooringdirect.co.uk

© 2019. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.