



# SPECTRA

expertly designed, perfectly waterproof

UK FLOORING DIRECT



## Product Data Sheet

**VIN-CLIC-PL-445**

Scan the QR code for fast access to this floor online

## Spectra Mountain Cliff Oak Plank Luxury Click Vinyl Flooring

With cool pale grey tones and a rich, swirling grain pattern, Spectra Mountain Cliff Oak Plank Luxury Click Vinyl Flooring will deliver a bold, modern look anywhere it's laid.

This true showstopper of a floor boasts an authentic textured surface that enhances the oak effect and comes in classic-size planks (191mm x 1316mm) that are ideal for creating a feeling of spaciousness in small and medium length rooms. Ready for any situation, Spectra Mountain Cliff Oak Plank Luxury Click Vinyl Flooring is hardwearing, compatible with underfloor heating and fully waterproof, making it suitable for use in moisture-prone and high-traffic areas such as hallways, kitchens and bathrooms as well as living areas.

A patented click system allows for fast and easy DIY fitting on top of underlay, no glue or nails required. As for maintenance, this is one easy-to-care-for floor: simply vacuum regularly and remove any marks with a cloth or mop dampened with water.

### Product Details

Code:	VIN-CLIC-PL-445
Brand:	Spectra
Construction:	LVT
Surface:	Authentic Textured
Profile:	Click System
Edge profile:	Micro bevel
Wear layer:	0.3mm
Thickness:	4.2mm
Width:	191mm
Length:	1316mm
Coverage per pack:	2.01m <sup>2</sup>
AC rating:	AC3 - Domestic

### Warranty

Residential:	12 Years
Commercial:	N/A

Disclaimer: To ensure your warranty is valid you must use the specified Acoustic Vinyl Underlay (ACC-UN-LC-03) as recommended with your Spectra Vinyl Flooring. As LVT has a maximum recommended surface temperature of 27°C, it's important to ensure this is not exceeded.  
NB: Please ask for full warranty terms and conditions

### Installation

Floated on underlay:	Yes
Over underfloor heating:	Yes, Water Systems up to 27 °C

### Technical

Water rating:	Waterproof
Technical Class:	Class 23-31
Fire resistance:	Bfl-S1
Formaldehyde emission:	E1
Slip resistance:	DS
Thermal resistance/conductivity:	EN 12664
Resistance to staining:	EN ISO 26987
Wear resistance:	EN ISO 10874

### UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ  
Tel: 02476 012840 | Fax: 02476 397828  
info@ukflooringdirect.co.uk  
ukflooringdirect.co.uk

© 2019. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.