



SPECTRA

expertly designed, perfectly waterproof

UK FLOORING DIRECT



Product Data Sheet

VIN-CLIC-PL-456

Scan the QR code for fast access to this floor online

Spectra Pearl Grey Oak Plank Luxury Click Vinyl Flooring

If you're after a grey wood-effect floor with a difference, Spectra Pearl Grey Oak Plank Luxury Click Vinyl Flooring is for you. A pale grey hue and a soft and subdued swirling grain, with no knots or streaks, give this floor a cool, contemporary look that's perfect for an industrial-style or minimalist interior.

This family-friendly LVT floor features an authentic textured surface for a realistic wood look and feel, and is fully waterproof so you can use it in demanding areas such as hallways, kitchens and bathrooms without worry. Its planks are a uniform size (191mm x 1316mm) that's ideal for helping to enhance the feeling of space in small and medium length rooms, while micro-bevelled edges give the finished floor a clean, modern appearance.

Spectra Pearl Grey Oak Plank Luxury Click Vinyl Flooring is fast and easy to install – even for DIYers – thanks to its patented click system, and is a fantastically low-maintenance option for busy spaces; simply vacuum regularly and clean occasionally with a damp mop.

Product Details

Code:	VIN-CLIC-PL-456
Brand:	Spectra
Construction:	LVT
Surface:	Authentic Textured
Profile:	Click System
Edge profile:	Micro bevel
Wear layer:	0.3mm
Thickness:	4.5mm
Width:	191mm
Length:	1316mm
Coverage per pack:	1.76m ²
AC rating:	AC3 - Domestic

Warranty

Residential:	12 Years
Commercial:	N/A

Disclaimer: To ensure your warranty is valid you must use the specified Acoustic Vinyl Underlay (ACC-UN-LC-03) as recommended with your Spectra Vinyl Flooring. As LVT has a maximum recommended surface temperature of 27°C, it's important to ensure this is not exceeded. NB: Please ask for full warranty terms and conditions

Installation

Floated on underlay:	Yes
Over underfloor heating:	Yes, Water Systems up to 27 °C

Technical

Water rating:	Waterproof
Technical Class:	Class 23-31
Fire resistance:	Bfl-S1
Formaldehyde emission:	E1
Slip resistance:	DS
Thermal resistance/conductivity:	EN 12664
Resistance to staining:	EN ISO 26987
Wear resistance:	EN ISO 10874

UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ
Tel: 02476 012840 | Fax: 02476 397828
info@ukflooringdirect.co.uk
ukflooringdirect.co.uk

© 2019. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.