



SPECTRA

expertly designed, perfectly waterproof

UK FLOORING DIRECT



Product Data Sheet

VIN-CLIC-PL-471

Scan the QR code for fast access to this floor online

Spectra Sea Salt Oak Plank Luxury Click Vinyl Flooring

Clean, elegant and understated, Spectra Sea Salt Oak Plank Luxury Click Vinyl boasts beautiful snowy tones and the subtlest of grain patterns, making it an ideal backdrop for contemporary and minimalist interior schemes.

This modern LVT floor is designed to withstand the rigours of family life; waterproof, hardwearing and easy to clean, it can safely be used in demanding areas such as bathrooms, hallways and kitchens as well as living spaces and bedrooms. Enhanced with an authentic textured surface for a realistic oak look and feel, Spectra Sea Salt Oak Plank Luxury Click Vinyl Flooring comes in micro-bevelled planks in a uniform size (191mm x 1316mm) that are ideal for balancing the proportions of small and medium length rooms.

Fast and easy to install – even for DIYers – thanks to its patented click system, this is a fantastically low-maintenance option for busy spaces; regular vacuuming and occasional damp mopping are all it takes to keep looking its best.

Product Details

Code:	VIN-CLIC-PL-471
Brand:	Spectra
Construction:	LVT
Surface:	Authentic Textured
Profile:	Click System
Edge profile:	Bevelled on 4 sides
Wear layer:	0.55mm
Thickness:	4.5mm
Width:	191mm
Length:	1316mm
Coverage per pack:	1.76m ²
AC rating:	AC5 - Commercial

Warranty

Residential:	20 Years
Commercial:	N/A

Disclaimer: To ensure your warranty is valid you must use the specified Acoustic Vinyl Underlay (ACC-UN-LC-03) as recommended with your Spectra Vinyl Flooring. As LVT has a maximum recommended surface temperature of 27°C, it's important to ensure this is not exceeded. NB: Please ask for full warranty terms and conditions

Installation

Floated on underlay:	Yes
Over underfloor heating:	Yes, Water Systems up to 27 °C

Technical

Water rating:	Waterproof
Technical Class:	Class 23-33-42
Fire resistance:	Bfl-S1
Formaldehyde emission:	E1
Slip resistance:	DS
Thermal resistance/conductivity:	EN 12664
Resistance to staining:	EN ISO 26987
Wear resistance:	EN ISO 10874

UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ
Tel: 02476 012840 | Fax: 02476 397828
info@ukflooringdirect.co.uk
ukflooringdirect.co.uk

© 2019. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.