



LiFE

VINYL

UK FLOORING DIRECT



Product Data Sheet

VIN-CLIC-PL-858

Scan the QR code for fast access to this floor online

Life Antique Grey Oak Plank Luxury Rigid Core Click Vinyl Flooring

Life Antique Grey Oak Plank Luxury Rigid Core Click Vinyl is a durable, easy to install, easy to care for floor that's the perfect match for the demands of everyday life. This 100% waterproof floor can be installed in all rooms, including conservatories with surface temperatures up to 60°C, kitchens, bathrooms, and rooms with underfloor heating systems up to 27°C. The rigid limestone core and scratch-resistant top layer have earned this floor an AC5 durability rating.

Its natural wood appearance mixed with a delicate grey hue will add a lasting charm to any home. Long and wide planks (1235mm x 232mm) will give the illusion of space in smaller areas, such as hallways, and be the perfect fit in larger rooms.

Product Details

Code:	VIN-CLIC-PL-858
Brand:	Life
Construction:	Rigid Core (SPC)
Surface:	Authentic Textured
Profile:	Click System
Edge profile:	Bevel
Thickness:	4mm
Width:	232mm
Length:	1235mm
Coverage per pack:	2.29
AC rating:	AC5 - Commercial
Wear Layer:	0.55mm

Warranty

Residential:	Lifetime
Commercial:	15 years

Installation

Floated on underlay:	Yes
Over underfloor heating:	Electric & Water Systems up to 27 °C

Technical

Water rating:	Waterproof
Technical Class:	33
Fire resistance:	Bfl-S1
Formaldehyde emission:	E1
Slip resistance:	R10
Thermal resistance/conductivity:	EN 12667
Resistance to staining:	EN 438-2
Wear resistance:	EN 13329
Effects of furniture leg:	NA
Effects of castor chair:	25,000R
Light fastness:	_ E ≤8
VOC emissions:	GGG certified
Thickness swelling:	_ 12%
Tolerance:	≤0.10% (width) 0.5mm (length) +0.13mm/-0.1mm (thickness)

UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ
Tel: 02476 012840 | Fax: 02476 397828
info@ukflooringdirect.co.uk
ukflooringdirect.co.uk

© 2020. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.