



LiFE

VINYL

UK FLOORING DIRECT



Product Data Sheet

VIN-CLIC-PL-871

Scan the QR code for fast access to this floor online

Life Hare Oak Plank Luxury Rigid Core Click Vinyl Flooring

A mixture of incredible style and impressive durability, our Life Rigid Core Vinyl range of flooring is perfect for a busy home. The easy to install click system is ideal for anyone looking to attempt their own DIY project, while it's AC5 rating ensures it can stand up to anything you throw at it. This 100% waterproof floor is perfect for a kitchen or bathroom, and can also be installed in conservatories thanks to its ability to withstand surface temperatures of 60°C as well as underfloor heating systems up to 27°C.

With stunning golden tones running through, Life Hare Oak Plank Rigid Core Click Vinyl is a versatile choice for a huge range of colour schemes. These natural looking planks include a genuine textured finish, giving it both the look and feel of real wood – you'll certainly be incorporating elegance and warmth with this flooring. At a classic length, the planks measure at 1235mm x 178mm and are ideal for any sized room in your home, so no matter your next refresh, this floor offers the perfect match.

Product Details

Code:	VIN-CLIC-PL-871
Brand:	Life
Construction:	Rigid Core (SPC)
Surface:	Authentic Textured
Profile:	Click System
Edge profile:	Painted
Thickness:	5mm
Width:	178mm
Length:	1235mm
Coverage per pack:	1.98
AC rating:	AC5 - Commercial
Wear Layer:	0.55mm

Warranty

Residential:	Lifetime
Commercial:	15 years

Installation

Floated on underlay:	Yes
Over underfloor heating:	Electric & Water Systems up to 27 °C

Technical

Water rating:	Waterproof
Technical Class:	33
Fire resistance:	Bfl-S1
Formaldehyde emission:	E1
Slip resistance:	R10
Thermal resistance/conductivity:	EN 12667
Resistance to staining:	EN 438-2
Wear resistance:	EN 13329
Effects of furniture leg:	No visible damage
Effects of castor chair:	NA
Light fastness:	_E ≤8
VOC emissions:	GGG certified
Thickness swelling:	_ 12%
Tolerance:	≤0.10% (width) 0.5mm (length) +0.13mm/-0.1mm (thickness)

UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ
Tel: 02476 012840 | Fax: 02476 397828
info@ukflooringdirect.co.uk
ukflooringdirect.co.uk

© 2021. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.