



LIFE

VINYL

UK FLOORING DIRECT



Product Data Sheet

VIN-CLIC-PL-877

Scan the QR code for fast access to this floor online

Life Autumn Oak Plank Luxury Rigid Core Click Vinyl Flooring

A mixture of incredible style and impressive durability, our Life Rigid Core Vinyl range of flooring is perfect for a busy home. The easy to install click system is ideal for anyone looking to attempt their own DIY project, while it's AC5 rating ensures it can stand up to anything you throw at it. This 100% waterproof floor with attached 1mm underlay is perfect for a kitchen or bathroom, and can also be installed in conservatories thanks to its ability to withstand surface temperatures of 60°C as well as underfloor heating systems up to 27°C.

Welcome in the beautiful, seasonal tones of Life Autumn Oak Plank Rigid Core Click Vinyl. With its lively swirling grain patterns and natural oak tone, this versatile floor will make the ideal addition to your home. The planks measure at 1532mm x 225mm and are ideal for any sized room, so no matter your next refresh, this floor offers the perfect match. These gorgeous planks include an authentic textured finish, offering both the look and feel of real wood, so you'll certainly be incorporating elegance and style with this flooring.

Product Details

Code:	VIN-CLIC-PL-877
Brand:	Life
Construction:	Rigid Core (SPC)
Surface:	Authentic Textured
Profile:	Click System
Edge profile:	Painted
Thickness:	5mm + 1mm Intergrated Underlay
Width:	225mm
Length:	1532mm
Coverage per pack:	1.38
AC rating:	AC5 - Commercial
Wear Layer:	0.55mm

Warranty

Residential:	Lifetime
Commercial:	15 years

Installation

Floated on underlay:	Yes
Over underfloor heating:	Electric & Water Systems up to 27 °C

Technical

Water rating:	Waterproof
Technical Class:	33
Fire resistance:	Bfl-S1
Formaldehyde emission:	E1
Slip resistance:	R10
Thermal resistance/conductivity:	EN 12667
Resistance to staining:	EN 438-2
Wear resistance:	EN 13329
Effects of furniture leg:	No visible damage
Effects of castor chair:	NA
Light fastness:	_E ≤8
VOC emissions:	GGG certified
Thickness swelling:	_ 12%
Tolerance:	≤0.10% (width) 0.5mm (length) +0.13mm/-0.1mm (thickness)

UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ
Tel: 02476 012840 | Fax: 02476 397828
info@ukflooringdirect.co.uk
ukflooringdirect.co.uk

© 2021. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.