



LiFE

VINYL

UK FLOORING DIRECT



Product Data Sheet

VIN-CLIC-PL-879

Scan the QR code for fast access to this floor online

Life Shell Oak Plank Luxury Rigid Core Click Vinyl Flooring

A mixture of incredible style and impressive durability, our Life Rigid Core Vinyl range of flooring is perfect for either a busy home, or office environment. The easy to install click system is perfect for anyone looking to attempt their own DIY project while the AC5 rating ensures it can stand up to anything you throw at it. This 100% waterproof floor with attached 1mm underlay is perfect for a kitchen or bathroom, and can also be installed in conservatories thanks to its ability to withstand surface temperatures of 60°C as well as underfloor heating systems up to 27°C.

With a mixture of lighter and darker tones throughout, providing a striking and relaxing design, our Life Shell Oak Plank Luxury Rigid Core Click Vinyl Flooring provides the natural feeling of wood with the incredible benefits of rigid core vinyl. This large wood-effect plank works perfectly in mid to large rooms, giving the room a sense of scale, while the natural lines, knots and textures imparts a feeling of authenticity to the vinyl planks.

Product Details

Code:	VIN-CLIC-PL-879
Brand:	Life
Construction:	Rigid Core (SPC)
Surface:	Authentic Textured
Profile:	Click System
Edge profile:	Painted
Thickness:	5mm + 1mm Intergrated Underlay
Width:	225mm
Length:	1532mm
Coverage per pack:	1.38
AC rating:	AC5 - Commercial
Wear Layer:	0.55mm

Warranty

Residential:	Lifetime
Commercial:	15 years

Installation

Floated on underlay:	Yes
Over underfloor heating:	Electric & Water Systems up to 27 °C

Technical

Water rating:	Waterproof
Technical Class:	33
Fire resistance:	Bfl-S1
Formaldehyde emission:	E1
Slip resistance:	R10
Thermal resistance/conductivity:	EN 12667
Resistance to staining:	EN 438-2
Wear resistance:	EN 13329
Effects of furniture leg:	No visible damage
Effects of castor chair:	NA
Light fastness:	_ E ≤8
VOC emissions:	GGG certified
Thickness swelling:	_ 12%
Tolerance:	≤0.10% (width) 0.5mm (length) +0.13mm/-0.1mm (thickness)

UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ
Tel: 02476 012840 | Fax: 02476 397828
info@ukflooringdirect.co.uk
ukflooringdirect.co.uk

© 2021. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.