



SPECTRA

expertly designed, perfectly waterproof

UK FLOORING DIRECT



Product Data Sheet

VIN-CLIC-TL-452

Scan the QR code for fast access to this floor online

Spectra Winter Frost Tile Luxury Click Vinyl Flooring

With a subtly patterned décor layer and an authentic textured surface that replicates the look and feel of unpolished concrete, this striking style will deliver a contemporary high-spec look along with all the practical benefits of modern LVT.

Spectra Winter Frost Tile Luxury Click Vinyl Flooring comes in a beautiful off-white hue – a fabulous backdrop for a minimalist or industrial scheme – and in fixed-size large (324mm x 655mm) tiles that are hugely versatile and work well in any size of room. Fast and easy to fit thanks to a DIY-friendly patented click system, they're finished with micro-bevelled edges to give a clean, modern look to the finished floor.

Spectra Winter Frost Tile Luxury Click Vinyl Flooring is compatible with underfloor heating and requires only minimal maintenance; simply vacuum regularly and wipe off any marks with a damp mop or cloth to keep it looking its best.

Product Details

Code:	VIN-CLIC-TL-452
Brand:	Spectra
Construction:	LVT
Surface:	Authentic texture
Profile:	Click System
Edge profile:	Micro bevel
Wear layer:	0.3mm
Thickness:	4.5mm
Width:	324mm
Length:	655mm
Coverage per pack:	1.49m ²
AC rating:	AC3 - Domestic

Warranty

Residential:	12 Years
Commercial:	N/A

Disclaimer: To ensure your warranty is valid you must use the specified Acoustic Vinyl Underlay (ACC-UN-LC-03) as recommended with your Spectra Vinyl Flooring. As LVT has a maximum recommended surface temperature of 27°C, it's important to ensure this is not exceeded. NB: Please ask for full warranty terms and conditions

Installation

Floated on underlay:	Yes
Over underfloor heating:	Yes, Water Systems up to 27 °C

Technical

Water rating:	Waterproof
Technical Class:	Class 23-31
Fire resistance:	Bfl-S1
Formaldehyde emission:	E1
Slip resistance:	DS
Thermal resistance/conductivity:	EN 12664
Resistance to staining:	EN ISO 26987
Wear resistance:	EN ISO 10874

UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ
Tel: 02476 012840 | Fax: 02476 397828
info@ukflooringdirect.co.uk
ukflooringdirect.co.uk

© 2019. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.