



SPECTRA

expertly designed, perfectly waterproof

UK FLOORING DIRECT



Product Data Sheet

VIN-CLIC-TL-468

Scan the QR code for fast access to this floor online

Spectra Slate Grey Tile Luxury Click Vinyl Flooring

Beautifully capturing the dramatic look of rough-hewn slate, this modern high-impact floor demands attention while delivering all the practical benefits of modern LVT.

Fully waterproof and compatible with underfloor heating, Spectra Slate Grey Tile Luxury Click Vinyl Flooring is suitable for use in demanding areas such as kitchens, hallways and bathrooms. It features plenty of colour variation and an all-over authentic textured surface that adds realism to the slate effect. Its bevel-edged tiles come in a uniform large size (324 x 655mm) that's extremely versatile, working well in both large and small rooms.

Coming with a 20-year warranty, Spectra Slate Grey Tile Luxury Click Vinyl Flooring is a great luxe-look low-maintenance option for family homes. Regular vacuuming and occasional damp mopping are all it takes to maintain its good looks, while a patented click system ensures it's fast and easy to fit, even for DIYers.

Product Details

Code:	VIN-CLIC-TL-468
Brand:	Spectra
Construction:	LVT
Surface:	Authentic texture
Profile:	Click System
Edge profile:	Bevelled on 4 sides
Wear layer:	0.55mm
Thickness:	4.5mm
Width:	324mm
Length:	655mm
Coverage per pack:	1.49m ²
AC rating:	AC5 - Commercial

Warranty

Residential:	20 Years
Commercial:	N/A

Disclaimer: To ensure your warranty is valid you must use the specified Acoustic Vinyl Underlay (ACC-UN-LC-03) as recommended with your Spectra Vinyl Flooring. As LVT has a maximum recommended surface temperature of 27°C, it's important to ensure this is not exceeded. NB: Please ask for full warranty terms and conditions

Installation

Floated on underlay:	Yes
Over underfloor heating:	Yes, Water Systems up to 27 °C

Technical

Water rating:	Waterproof
Technical Class:	Class 23-33-42
Fire resistance:	Bfl-S1
Formaldehyde emission:	E1
Slip resistance:	DS
Thermal resistance/conductivity:	EN 12664
Resistance to staining:	EN ISO 26987
Wear resistance:	EN ISO 10874

UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ
Tel: 02476 012840 | Fax: 02476 397828
info@ukflooringdirect.co.uk
ukflooringdirect.co.uk

© 2019. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.