



SPECTRA

expertly designed, perfectly waterproof

UK FLOORING DIRECT



Product Data Sheet

VIN-DRY-PL-477

Scan the QR code for fast access to this floor online

Spectra Rustic Natural Oak Plank Luxury Glue Down Vinyl Flooring

With rich grain markings, a homely warm oak tone and an incredibly realistic wood look, Spectra Rustic Oak Natural Plank Luxury Glue Down Vinyl Flooring will bring instant country-style character and charm to even the most pared-back of schemes. But don't be fooled by its good looks, this tough and waterproof LVT floor is a superbly practical option for busy spaces.

Creating a lived-in vintage vibe wherever it's laid, Spectra Rustic Oak Natural Plank Luxury Glue Down Vinyl Flooring is safe for use in demanding areas such as hallways, kitchens and bathrooms. Its planks are a uniform size (196mm x 1320mm) ideal for creating a classic look while enhancing the feeling of space in small and medium rooms, and are enhanced with a true textured surface that follows the pattern of the grain for the ultimate authentic look.

A professional or a keen D.I.Yer with experience using adhesive is required to offer enhanced durability and resilience against any unwanted shifting. Spectra Rustic Oak Natural Plank Luxury Glue Down Vinyl Flooring comes with a 20-year residential warranty and is a breeze to maintain: simply vacuum regularly and clean occasionally with a damp mop.

Product Details

Code:	VIN-DRY-PL-477
Brand:	Spectra
Construction:	LVT
Surface:	Authentic Surface
Profile:	Glue Down/Dry back
Edge profile:	Micro Bevel
Wear layer:	0.55mm
Thickness:	2.5mm
Width:	196mm
Length:	1320mm
Coverage per pack:	3.62m ²
AC rating:	AC5 - Commercial

Warranty

Residential:	20 Years
Commercial:	10 Years

Disclaimer: As LVT has a maximum recommended surface temperature of 35°C, it's important to ensure this is not exceeded. NB: Please ask for full warranty terms and conditions

Installation

Floated on underlay:	Yes
Fully bonded:	Yes
Over underfloor heating:	Yes, Water Systems up to 27 °C

Technical

Water rating:	Waterproof
Technical Class:	Class 23-33-42
Fire resistance:	Bfl-S1
Formaldehyde emission:	E1
Slip resistance:	DS
Thermal resistance/conductivity:	EN 12664
Resistance to staining:	EN ISO 26987
Wear resistance:	EN ISO 10874

UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ
Tel: 02476 012840 | Fax: 02476 397828
info@ukflooringdirect.co.uk
ukflooringdirect.co.uk

© 2020. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.