



SPECTRA

expertly designed, perfectly waterproof

UK FLOORING DIRECT



Scan the QR code for fast access to this floor online

Product Data Sheet

VIN-DRY-PL-478

Spectra Columbia Pine White Plank Luxury Glue Down Vinyl Flooring

With subtle white and grey hues that bring elegance to its lively authentic grain, Spectra Columbia Pine White Plank Luxury Glue Down Vinyl Flooring will create a bright and chic look in modern homes.

This striking floor has a textured surface that follows the grain patterns beneath for an authentic wood look and feel, and is warm underfoot and fully waterproof – making it an ideal choice for bathrooms.

The wide, classic-length planks (163mm x 988mm) will look fantastic in a wide range of spaces but are particularly well suited to creating a space enhancing effect in small and medium rooms. A professional or a keen D.I.Yer with experience using adhesive is required to offer enhanced durability and resilience against any unwanted shifting.

Tough as well as stylish, Spectra Columbia Pine White is 2mm thick and has an AC3 Domestic rating, making it suitable for any room in the home. With a 12-year residential warranty, it's also blissfully easy to care for; regular vacuuming and occasional damp-mopping are all that's required to ensure it stays looking fabulous.

Product Details

Code:	VIN-DRY-PL-478
Brand:	Spectra
Construction:	LVT
Surface:	Authentic Textured
Profile:	Glue Down/Dry back
Edge profile:	Micro Bevel
Wear layer:	0.3mm
Thickness:	2mm
Width:	163mm
Length:	988mm
Coverage per pack:	3.87m ²
AC rating:	AC3 - Domestic

Warranty

Residential:	12 Years
Commercial:	5 Years

Disclaimer: As LVT has a maximum recommended surface temperature of 35°C, it's important to ensure this is not exceeded. NB: Please ask for full warranty terms and conditions

Installation

Floated on underlay:	Yes
Fully bonded	Yes
Over underfloor heating:	Yes, Water Systems up to 27 °C

Technical

Water rating:	Waterproof
Technical Class:	Class 23-31
Fire resistance:	Bfl-S1
Formaldehyde emission:	E1
Slip resistance:	DS
Thermal resistance/conductivity:	EN 12664
Resistance to staining:	EN ISO 26987
Wear resistance:	EN ISO 10874

UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ
Tel: 02476 012840 | Fax: 02476 397828
info@ukflooringdirect.co.uk
ukflooringdirect.co.uk

© 2020. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.