



SPECTRA

expertly designed, perfectly waterproof

UK FLOORING DIRECT



Product Data Sheet

VIN-DRY-PL-479

Scan the QR code for fast access to this floor online

Spectra Rustic Bark Oak Plank Luxury Glue Down Vinyl Flooring

Capturing the character and beauty of dark oak in astonishing detail, Spectra Rustic Bark Oak Plank Luxury Glue Down Vinyl Flooring has a warm brown tone and a rich grain enlivened with cracks and knots. With bags of vintage charm, it's a fabulous choice if you want to give a room a warm and inviting vibe.

A great fit-and-forget option for family homes, Spectra Rustic Bark Oak Plank Luxury Glue Down Vinyl Flooring is tough, fully waterproof and compatible with underfloor heating, and can safely be used in demanding areas such as hallways, kitchens and bathrooms. Its planks are a classic size (196mm x 1320mm) ideal for enhancing the feeling of space in small and medium length rooms, and are finished with a premium true texture surface that follows the surface pattern of the grain for the ultimate in realism.

A professional or a keen D.I.Yer with experience using adhesive is required to offer enhanced durability and resilience against any unwanted shifting. Spectra Rustic Bark Oak Plank Luxury Glue Down Vinyl Flooring comes with a 20-year residential warranty and is a breeze to maintain: simply vacuum regularly and clean occasionally with a damp mop.

Product Details

Code:	VIN-DRY-PL-479
Brand:	Spectra
Construction:	LVT
Surface:	Authentic Surface
Profile:	Glue Down/Dry Back
Edge profile:	Micro Bevel
Wear layer:	0.55mm
Thickness:	2.5mm
Width:	196mm
Length:	1320mm
Coverage per pack:	3.62m ²
AC rating:	AC5 - Commercial

Warranty

Residential:	20 Years
Commercial:	10 Years

Disclaimer: As LVT has a maximum recommended surface temperature of 35°C, it's important to ensure this is not exceeded. NB: Please ask for full warranty terms and conditions

Installation

Floated on underlay:	Yes
Fully bonded	Yes
Over underfloor heating:	Yes, Water Systems up to 27 °C

Technical

Water rating:	Waterproof
Technical Class:	Class 23-33-42
Fire resistance:	Bfl-S1
Formaldehyde emission:	E1
Slip resistance:	DS
Thermal resistance/conductivity:	EN 12664
Resistance to staining:	EN ISO 26987
Wear resistance:	EN ISO 10874

UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ
Tel: 02476 012840 | Fax: 02476 397828
info@ukflooringdirect.co.uk
ukflooringdirect.co.uk

© 2020. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.