



# SPECTRA

expertly designed, perfectly waterproof

UK FLOORING DIRECT



## Product Data Sheet

**VIN-DRY-TL-482**

Scan the QR code for fast access to this floor online

## Spectra Thunder Cloud Stone Tile Luxury Glue Down Vinyl Flooring

With dark and stormy grey tones that demand attention, Spectra Thunder Cloud Stone Tile Luxury Vinyl Glue Down Flooring is a true statement floor, that's perfect for setting a modern mood in any space.

Its authentic textured surface and subtly mottled décor layer give it an incredibly realistic stone look and feel, but this floor delivers on the performance front, too. Compatible with underfloor heating and fully waterproof, it's safe for use in demanding areas such as kitchens, utility rooms and bathrooms. It comes in fixed-size large (329mm x 659mm) tiles that work well in any size of room and ensure a clean, contemporary finish.

Spectra Thunder Cloud Stone Tile Luxury Glue Down Vinyl Flooring will make a valuable addition to a busy home. Regular vacuuming and occasional damp mopping are all it takes to maintain its good looks. A professional or a keen D.I.Yer with experience using adhesive is required to offer enhanced durability and resilience against any unwanted shifting.

### Product Details

Code:	VIN-DRY-TL-482
Brand:	Spectra
Construction:	LVT
Surface:	Authentic texture
Profile:	Glue Down/Dry back
Edge profile:	Micro bevel
Wear layer:	0.3mm
Thickness:	2mm
Width:	329mm
Length:	659mm
Coverage per pack:	3.9m <sup>2</sup>
AC rating:	AC3 - Domestic

### Warranty

Residential:	12 Years
Commercial:	5 Years

Disclaimer: As LVT has a maximum recommended surface temperature of 35°C, it's important to ensure this is not exceeded. NB: Please ask for full warranty terms and conditions

### Installation

Floated on underlay:	Yes
Fully bonded:	Yes
Over underfloor heating:	Yes, Water Systems up to 27 °C

### Technical

Water rating:	Waterproof
Technical Class:	Class 23-31
Fire resistance:	Bfl-S1
Formaldehyde emission:	E1
Slip resistance:	DS
Thermal resistance/conductivity:	EN 12664
Resistance to staining:	EN ISO 26987
Wear resistance:	EN ISO 10874

### UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ  
Tel: 02476 012840 | Fax: 02476 397828  
info@ukflooringdirect.co.uk  
ukflooringdirect.co.uk

© 2020. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.