



SPECTRA

expertly designed, perfectly waterproof

UK FLOORING DIRECT



Product Data Sheet

VIN-DRY-TL-483

Scan the QR code for fast access to this floor online

Spectra Natural Limestone Tile Luxury Glue Down Vinyl Flooring

With rich colour variation and organic patterns inspired by nature, this truly beautiful LVT floor perfectly recreates the sumptuous look and feel of stone while offering all the practical benefits that come as standard with the latest high-quality LVT.

In a natural colourway enhanced with the pale brown and grey streaks that characterise unpolished limestone. Spectra Natural Limestone Tile Luxury Glue Down Vinyl Flooring will bring a timeless high-end look to any room, and would make a striking addition to a spa-style bathroom or country-style kitchen. Boasting an authentic textured surface, this fully waterproof, family-friendly floor comes in fixed-sized large (329mm x 659mm) tiles that are hugely versatile and work well in any sized room.

Spectra Natural Limestone Tile Luxury Glue Down Vinyl Flooring is compatible with underfloor heating and requires only minimal maintenance; simply vacuum regularly and wipe off any marks with a damp mop or cloth to keep it looking its best. A professional or a keen D.I.Yer with experience using adhesive is required to offer enhanced durability and resilience against any unwanted shifting.

Product Details

Code:	VIN-DRY-TL-483
Brand:	Spectra
Construction:	LVT
Surface:	Authentic texture
Profile:	Glue Down/Dry back
Edge profile:	Micro bevel
Wear layer:	0.3mm
Thickness:	2mm
Width:	329mm
Length:	659mm
Coverage per pack:	3.9m ²
AC rating:	AC3 - Domestic

Warranty

Residential:	12 Years
Commercial:	5 Years

Disclaimer: As LVT has a maximum recommended surface temperature of 35°C, it's important to ensure this is not exceeded. NB: Please ask for full warranty terms and conditions

Installation

Floated on underlay:	Yes
Fully bonded:	Yes
Over underfloor heating:	Yes, Water Systems up to 27 °C

Technical

Water rating:	Waterproof
Technical Class:	Class 23-31
Fire resistance:	Bfl-S1
Formaldehyde emission:	E1
Slip resistance:	DS
Thermal resistance/conductivity:	EN 12664
Resistance to staining:	EN ISO 26987
Wear resistance:	EN ISO 10874

UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ
Tel: 02476 012840 | Fax: 02476 397828
info@ukflooringdirect.co.uk
ukflooringdirect.co.uk

© 2020. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.