



# SPECTRA

expertly designed, perfectly waterproof

UK FLOORING DIRECT



## Product Data Sheet

### VIN-DRY-TL-484

Scan the QR code for fast access to this floor online

## Spectra Dark Grey Stone Tile Luxury Dryback Vinyl Flooring

If you're seeking the beautiful look of stone but want a floor that's easy to care for, Spectra Dark Grey Stone Tile Luxury Glue Down Vinyl Flooring fits the bill. With a modern, clean grey slate look and a textured surface, this contemporary stone-effect floor will create a fresh and timeless look in any setting.

Offering good coverage for fast installation, the tiles measure 329mm x 659mm, a versatile size suited for use in both large and small rooms. A professional or a keen D.I.Yer with experience using adhesive is required to offer enhanced durability and resilience against any unwanted shifting.

Fully waterproof – making it an ideal choice for bathrooms – Spectra Dark Grey Stone comes with an R10 slip rating and is naturally warm underfoot. With a thickness of 2mm, a 12-year residential warranty and an AC3 Domestic rating, it's resistant to scuffs and marks. Durable enough for any room in the home; simply vacuum regularly and damp-mop from time to time to keep it looking fabulous.

### Product Details

Code:	VIN-DRY-TL-484
Brand:	Spectra
Construction:	LVT
Surface:	Authentic Textured
Profile:	Glue Down/Dry back
Edge profile:	Micro Bevel
Wear layer:	0.3mm
Thickness:	2mm
Width:	329mm
Length:	659mm
Coverage per pack:	3.9m <sup>2</sup>
AC rating:	AC3 - Domestic

### Warranty

Residential:	12 Years
Commercial:	5 Years

Disclaimer: As LVT has a maximum recommended surface temperature of 35°C, it's important to ensure this is not exceeded. NB: Please ask for full warranty terms and conditions

### Installation

Floated on underlay:	Yes
Fully bonded:	Yes
Over underfloor heating:	Yes, Water Systems up to 27 °C

### Technical

Water rating:	Waterproof
Technical Class:	Class 23-31
Fire resistance:	Bfl-S1
Formaldehyde emission:	E1
Slip resistance:	DS
Thermal resistance/conductivity:	EN 12664
Resistance to staining:	EN ISO 26987
Wear resistance:	EN ISO 10874

### UK Flooring Direct

Unit 2 Logix Road, Hinckley, Leicestershire LE10 3BQ  
Tel: 02476 012840 | Fax: 02476 397828  
info@ukflooringdirect.co.uk  
ukflooringdirect.co.uk

© 2020. This technical data sheet was written by UK Flooring Direct Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this technical data sheet are for illustration purposes only.